



普通环保汽车线束胶粘带 UD110N Tape For Wire Harness

特性: 环保无铅汽车线束胶粘带是由优质的增塑型 PVC 薄膜涂布高性能压敏胶制作而成。具有优良的电气性能及柔软性, 不受大多数化学物质及湿气的影晌。符合 RoHS 指令和 REACH 法规要求。可避免普通电工胶带中铅、镉等有毒物质对人体的慢性伤害, 确保使用者的长期安全。不含 DBP, 增塑剂, 铅和镉。符合 RoHS 和 REACH 要求。

Application: It is specifically designed for wire harness application, wrapped wires with a half-lap is better, the last layer should be no tension to prevent flagging.

Technical Data:
UD110N 技术指标:

性能 Properties		单位 Unit	典型数据 Specification		测试方法 Test Method
			UD110N		
			UD110N		
总厚度	mm		0.110		ASTM D1000
Total Thickness	mm		0.110		ASTM D1000
拉伸强度	N/cm		15		ASTM D1000
Tensile Strength	N/cm		15		ASTM D1000
伸长率	%		150		ASTM D1000
Elongation	%		150		ASTM D1000
剥离强度					
Adhesion Strength					
• 对钢板	N/cm		1.0		ASTM D1000
• to steel	N/cm		1.0		ASTM D1000
• 对基材	N/cm		1.0		
• to Backing	N/cm		1.0		
耐电压等级	V		600		UL510
Dielectric Breakdown	V		600		UL510
耐温等级	℃		80		ASTM D1000
Temperature Resistance	℃		80		ASTM D1000
重金属含量					
Content of Heavy Metal					
• 铅、镉	ppm		30 30		US EPA 3052
• Lead, Cadmium	ppm		30 30		US EPA 3052
• 汞、六价铬	ppm		10 10		US EPA 3060A
• Mercury, Chromium(VI)	ppm		10 10		US EPA 3060A
• 多溴联苯、多溴联苯醚	ppm		10 10		US EPA 540C
• Polybrominated biphenyls	ppm		10 10		US EPA 540C
Polybrominated biphenyl ethers					

Other properties

- Color: Black and other 颜色: 黑色及其它颜色
- Surface Texture: Matt 表面结构: 雾面或光面
- Shelf Life: 12 months when stored in original carton at 23°C × 65% R.H. 储存期: 23°C × 65%RH 下, 在原包装箱中可储存 12 个月。

Availability

- Standard length: 9m, 18m, 20m 标准长度: 9m, 18m, 20m
- Standard width: 19mm 标准宽度: 19mm
- Standard diameter of core: 32mm, 38mm 标准纸心的内径: 32mm, 38mm

Important Notice to Purchaser: All statements, information and recommendations contained herein are based on tests we believe to be reliable, before using, users shall determine the suitability of the product for their intended uses.

敬告用户:

以上所有数据及信息是基于我们的测试结果, 用户在使用之前必须针对所期望的用途确定产品的适用性。