



地址:涿州市开发区工业园区燕邑东路9号

电话: (86-312)3975959 网址: www.yongletape.com

FP110AS Tape For Wire Harness

VOC Free and Lead-free

Description: FP110AS is a pressure sensitive PVC tape with acrylic based adhesive. It is suitable for continuous use at 125°C with good electrical, flammability and soft property, not influenced by most chemical substances and humidity. It complies with RoHS and REACH requirements.

HeBei Huaxia FP110AS Harness Wrap Tape meets and exceeds the requirements of GM.

Features: --Highly conformable

> -- Pressure sensitive --Flame resistant

--Black

--VOC free and low odor -- Meet RoHS and REACH

Technical Data:

Properties	unit	Value	Test Method
Total Thickness	mm	0.110	ASTM D1000
Tensile Strength	N/cm	21	ASTM D1000
Elongation	%	200	ASTM D1000
Adhesion			ASTM D1000
• to steel	N/cm	1.3	
• to Backing	N/cm	1.5	
Unwind force	N/ cm	3.5	ASTM D1000
Flammability	mm/min	<100	ISO3795
Temperature Rating		С	GMW16740

Data in table represent typical test results and are not to be used for specification purposes. The product users should make his/her own tests to determine the product's suitability for the intended use.

Standard Sizes:

• Width: 19mm • Length: 20m;

• Diameter of core: 38mm;

Color: Black **Recommended Uses:**

Use as permanent wrap on cables and wiring harness for automobile. The recommended application method is with 50% overlap and do not apply tension at last layer.

Shelf Life:

2 years in the original package.