



Tape For Wire Harness VOC Free and Lead-free

Description: It is a pressure sensitive PVC tape with acrylic based adhesive. It is suitable for continuous use at 125°C with good electrical, flammability and soft property, not influenced by most chemical substances and humidity. It complies with RoHS and REACH requirements.

Features:

- Highly conformable-
- Pressure sensitive
- Flame resistant Black
- VOC free and low odor
- Meet RoHS and REACH

Technical Data:

Properties	unit	Value	Test Method
Total Thickness	mm	0.110	ASTM D1000
Tensile Strength	N/cm	21	ASTM D1000
Elongation	%	200	ASTM D1000
Adhesion			ASTM D1000
• to steel	N/cm	1.3	
• to Backing	N/cm	1.5	
Unwind force	N/ cm	3.5	ASTM D1000
Flammability	mm/min	<100	ISO3795
Temperature Rating		C	GMW16740

Data in table represent typical test results and are not to be used for specification purposes. The product users should make his/her own tests to determine the product's suitability for the intended use.

Standard Sizes:

- Length: 20m;
- Width: 19mm
- Diameter of core: 38mm;

Color: Black

Recommended Uses:

Use as permanent wrap on cables and wiring harness for automobile. The recommended application method is with 50% overlap and do not apply tension at last layer.

Shelf Life:

1 years in the original package.