



## HM500060 Foam Tape

**Description:** HM is PU foam coated with aggressive acrylic-based adhesive with good characteristics. It is highly conformable and unaffected by most chemicals and moisture, good noise reduction.

**Application:** It is specifically designed for wrapping automotive wire harness.

**Technical Data:**

Properties	unit	Physical data	Test method
		HM500060	
Backing		PU Foam	--
Total Thickness	mm	5.0	ASTM D1000
Tensile Strength	N/cm	5.0	ASTM D1000
Elongation	%	100	ASTM D1000
Adhesion Strength ·to steel·	N/cm	Foam destroy	ASTM D1000
Temperature Range	°C	60	--
Content of Heavy Metal·			
·Lead, Cadmium	ppm	30	US EPA3052
·Mercury, Chromium(VI)	ppm	10	US EPA3060A
·Polybrominated bipheyls	ppm	10	US EPA3540C
Polybrominated bipheyl ethers			

### Other properties

- Color : grey
- Shelf Life: 12 months when stored in original carton at 23 °C × 65%R.H.

### Availability

- Standard length: 5m
- Standard width: 25mm , 40mm, 50mm

**\*other sizes upon request**

**Important Notice to Purchaser:** All statements, information and recommendations contained herein are based on tests we believe to be reliable, before using, users shall determine the suitability of the product for their intended uses.