



HX9532 Non Woven Cloth Tape

Application: This product is used for wire harness wrapping in the automotive industry and is preferably used to meet the delicate requirements inside the cars. High-quality non-woven fabric can ensure good rotting resistance, abrasion resistance, thermal resistance and aging resistance. This product has excellent noise-reduction effect and constant unwind force. This product is also very flexible and supple is easy to tear by hand.

Technical Data:

Properties	unit	Value	Test method
Total Thickness	mm	1.0±0.1	ASTM D1000
180° peel strength to steel	N/cm	2.0	ASTM D1000
180° peel strength to backing	N/cm	2.0	ASTM D1000
Tensile Strength	N/cm	35	ASTM D1000
Elongation at break	%	10	ASTM D1000
Usage Temperature	°C	-40/+105	LV-312
Low-speed unwind force	N/19mm	2--8	ASTM D1000
Flammability	Burn rate ≤ 100mm/min	PASS	LV-312

Properties

- Colour : Black
- Structure: Thick non-woven fabric in combination with high-adhesion PSA
- Advantages:
 - high adhesive force —stable against rotting —flexible and supple
 - very high noise reduction effect —excellent media resistance —high temperature stability
 - extremely soft surface —easy to handle (no inter liner)
- Shelf life: 12months is the original package at 23°C and 65% relative humidity.

Normal Size:

- Standard length: 5m
- Standard width: 19mm 25mm
- Standard inner diameter of the paper core: 38mm

Important Notice to Purchaser: All statements, information and recommendations contained herein are based on tests we believe to be reliable, before using, users shall determine the suitability of the product for their intended uses.